



Testing Performed under NSF/ANSI Standards 53 and P473 in accordance with the California Department of Health Services Drinking Water Treatment Device Program. This system has been tested according to NSF/ANSI 53 & P473 for reduction of the substances listed below. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI 53 and P473.

Performance Data for the OptimH2O Whole House Filter					
Model	Replacement	Micron Rating	Size	Operating Pressure Range	Operating Temp. Range
EQ-OPTM	EQ-OPTM-R	0.5	8" x 42"	20-125 psig / 1.38-8.6 bar	34-120° F / 1-50° C
<b>Electrical Requirements</b>			<b>Rated Capacity</b>		
Grounded & Unswitched 115V outlet, 3 AAA Batteries			106,750 Gallons @ 4.82GPM / 404,092 L @ 18.25 LPM		
<b>NSF/ANSI 53</b>			<b>NSF P473</b>		
99.62% lead and cysts reduction			98.2% PFOA/PFOS reduction		
Distributed by: Aquasana, Inc. 6310 Midway Road · Haltom City, Texas 76117 · 866-662-6885					



The OptimH2O filter is IAPMO Tested and Certified to NSF/ANSI Standard 53 to reduce both soluble and particulate forms of lead and cysts, and to NSF/ANSI Standard P473 to reduce perfluorooctanoic acid (PFOA) and perfluorooctane sulfonate (PFOS).

Internally tested Performance Data for the Aquasana Whole House Water Filter		
Parameter	Influent Challenge Chlorine	Overall % reduction
Chlorine, Chloramines Reduction	3 mg/L ±10%	>90%



**Do not use with water that is microbiologically unsafe or of unknown water quality without adequate disinfection before or after the system.**

- All contaminants reduced by this filter are listed.
- Not all contaminants listed may be present in your water.
- Does not remove all contaminants that may be present in tap water.
- Manufactured from NSF/ANSI standard 61 and California Prop 65 Compliant certified coconut shell carbon and raw materials.



Filter is only to be used with cold water.



Filter usage must comply with all state and local laws.



Testing was performed under standard laboratory conditions, actual performance may vary.



Systems certified for cyst reduction may be used on disinfected waters that may contain filterable cysts.



See owner's manual for general installation conditions and needs plus manufacturer's limited warranty.